

Panther Vs Panther PRO



Panther



Panther PRO



Size	H 320 x W 80 x D 55 mm	H 320 x W 80 x D 55 mm
Weight	447g	447g
Operating Temperature	0°C to 50°C	0°C to 50°C
Ingress Protection Rating	IP44	IP44
Probe Options	Short & Long Probe	Short & Long Probe
Technology	Micro Thermal Conductivity	Micro Thermal Conductivity
Sensitivity (Helium)	5 x 10 ⁻⁶ (cc/sec)	5 x 10 ⁻⁶ (cc/sec)
Available Measurement Units	cc/sec, g/year, ppm, mg/m ³ , %Vol	cc/sec, g/year, ppm, mg/m ³ , %Vol
Sensitivity Levels	3 (x100, x10, x1)	3 (x100, x10, x1)
Response Time	T90 = 1 second	T90 = 1 second
Sampling Method	Internal Pump	Internal Pump

Panther Vs Panther PRO



Panther



Panther PRO



Audible Alarm	✓	✓
Vibration Alarm	✓	✓
Visual Alarm	✓	✓
Bluetooth	✗	✓
Integrated Torch	✓	✓
Internal gas table	✓	✓
Datalogging	✗	10 days continuous
PC Software	✓	✓
Data Export	✗	✓
Battery Life	20 hours	20 hours
Battery Type	Li-ion Battery	Li-ion Battery